

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8111)

Set a laurel post 3" sq., 3 ft. long, 18" in the ground, marked ¼ S on the N face for the ¼ sec. cor. from which
A cedar, 30" dia., bears S.60°W., 56 lks., mkd: ¼ S BT.
A fir, 36" dia., bears N.60°W., 119 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Jan. 1967 - C.S. File 54/36-41

Found - Orig. 30" Cedar, now 56", S.60°W., 37.0 ft., bark scribe visible "¼S BT".

Orig. 36' Fir, now down & burned.

Set brass Cap at Cor. MKD: County Surveyors Office 1967 T31S R8W ¼ S 25 S 36

New BTs- 7" D.Fir S.50°W. 18.6 ft. mkd. ¼ S36 CS BT.
16" D.Fir N.17°E., 44.0 ft.

This cor. lies on E slope about 330 ft. from ridge top, yellow tag on line west of corner.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page)(s) 16188-9)

The ¼ sec. cor. of secs. 25 & 36, perpetuated & recorded by James W. Byron, County Surveyor, in 1967, monumented with an iron post, 1¼" dia., firmly set, projecting 15" above ground, with brass cap (properly) mkd:

from which the remains of the orig. BTs

A decayed fir stump, size indeterminate, bears N.60°W., 119 lks., no marks visible.

A cedar, 57" dia., bears S.60°W., 62 lks., with scribe marks ¼ S BT visible on partially open blaze. (Rec. 56 lks.)

and BTs mkd. by Byron

A fir, 18" dia. bears N.17°E., 66½ lks. with healed blaze.

A fir, 10" dia., bears S.50°W., 29 lks. with healed blaze.