

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8113)  
-----  
Set a fir post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S on the NW face, fro the ¼ sec. cor. and from which  
A S.Pine, 16" dia., bears N.20°E., 30 lks., mkd: ¼ S BT.  
A fir, 14" dia., bears S.12°E., 26 lks., mkd: ¼ S BT.

BLM Dependent resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO Records Vol. 41 Page(s) 16191)  
-----  
Point for the ¼ sec. cor. of secs. 24 & 25, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:  
T31S R8W  
¼     S 24  
          S 25  
          1977

from which  
A fir, 5" dia., bears N.45°E., 15 lks., mkd: ¼ S24 BT.  
A fir, 8" dia., bears S.56¼°E., 44 lks., mkd: ¼ S25 BT.