

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8115)

Set a fir post 3 ft. long, 3" sq., 18" in the ground & marked ¼ S on the N side for the ¼ sec. cor., from which
An Oak, 24" dia., bears N.13°W., 71 lks., mkd: ¼ S BT.
A Fir, 12" dia., bears S.65°E., 18 lks., mkd: ¼ S BT.

BLM Resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors, under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO records Vol. 41 Page(s) 16195)

Point for ¼ sec. cor. of secs. 13 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T 31 S R 8 W
 S 13
¼ S 24
1977

from which

A fir, 9" dia., bears N.6½°E., 58½ lks., mkd: ¼ S13 BT.
A madrone, 8" dia., bears S.72°E., 24½ lks. mkd: ¼ S24 BT.

Mark Smalley - For: Roseburg Resources - 5/2002 - C.S. File 65/44-11

Found - 1977 BLM IPBC.
17" Fir N.6½°E., 58½ lks., (38.6') good condition, healed face.

Unrecorded 13" Fir with healed face. We put a Roseburg Forest Products BT tag with information.
13" Fir West 21.5' good condition, healed face.

New - 2001 - 9" Fir S.1°E., 16.1' scribed "¼ S BT"
2001 - 8" Fir N.32°W., 6.6' scribed "¼ S BT"