

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8117)

Set a cedar post 3 ft. long, 3" sq. marked ¼ S on N face for the ¼ sec. cor. and from which
 A fir, 16" dia., bears S.15°E., 20 lks., mkd: ¼ S BT.
 A fir, 16" dia., bears N.70°W., 59 lks., mkd: ¼ S BT.

Reported as not found by DCSO (1966?) - C.S. File 54/28-110

David Edwards - For: Seneca Jones Timber & Roseburg Resources
- Nov. 2017 - M173-76

Proportionate position.
Set - 5/8"x30" steel rebar with 2½" dia., alum. cap marked as per the 2009 BLM manual & marked "LS 2339" and "2017"
 A 10" dia., fir scribed "¼ S13 BT" bears S.19°E., 25.2'
No other live trees area available due to fire.
Set - 6' steel posts 2 ft. north and 2 ft. S.89°W.