

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION 1/4 cor. for Sec. 1; & S. 36, T30-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7312-13)

Set a Laurel post 3 ft. long, 3" sq., 18" in the ground for the 1/4 sec. cor. mkd. 1/4 S on the N. side of same, from which
A Pine 24" dia., bears S.25°E., 18 lks. dist. mkd. 1/4 S BT
A Pine 30" dia., bears N.60°E., 27 lks. dist. mkd. 1/4 S BT

Arthur Evans -For: Martin Bros. Box Co. - April 1956 - C.S. File 42/197-2

Found 2 Original BTs:
24" Pine S.25°E., 18 lks., rotten snag.
30" Pine N.60°E., down and rotten.
Set 4" x 4" x 48" D.Fir post, from which new BTs:
6" W.Fir N.36°E., 33 lks. mkd. 1/4 S36 RE 2741 BT.
16" D.Fir S.24°W., 27.5 ft. mkd. 1/4 S1 RE 2741 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - March 31, 1971 - C.S. File 53/67-17

Found - 4 x 4 post at 1/4 corner.
6" now 8" W.Fir, N.31°E., (Rec. N.36°E.) 21.8 ft., open for scribe "BT".
16" now 19" D.Fir S.24°W., 18.1 ft., no scribe visible on face.

I do not find original Pine, as notes. Do find Pine stob S.25°E., 14.9 ft. (Rec. 11.9 ft.) This stob badly burnt and decayed. No trace of NE. BT, burn in area very old, doubt original ever found.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 8 W
1/4 S 36
S 1
1971

Reblaze and rescribe:
19" D.Fir S.24°W., 18.1 ft. scribed 1/4 S1 CS BT.

Fd. OK, Dec. 1981 by H. Johnstone - M 89-79