

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 36; & 30, 31 of T31-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8030)

-----  
Set a Pine post 4 ft. long, 4" sq., 22" in the ground, marked T31S R7W S30 on NE. face; S31 on SE. face; S36 on SW. face; R8W S25 on NW. face; also one notch on S. and five notches on N. angle of same for the cor. to secs. 25, 30, 31 and 36, from which

- A Pine 42" dia., bears N.82°E., 192 lks. dist. mkd. T31S R7W S30 BT.
- A Pine 12" dia., bears S.68°E., 122 lks. dist. mkd. T31S R7W S31 BT.
- A Pine 36" dia., bears S.62°W., 250 lks. dist. mkd. T31S R8W S36 BT.
- A Pine 40" dia., bears N.35°W., 144 lks. dist. mkd. T31S R8W S25 BT.

Douglas Co. Surveyors Office - John Powell and W. Penley, crew - April 30, 1970 - C.S. File 54/36-17

-----  
Found - 12" now 48" Pine, S.68°E., 79.5 ft., tree opened for scribe.  
36" now 48" Pine, S.62°W., 165.0 ft., open and find about 85 yrs. No trace of burl.  
42" Pine, now burnt stob, N.82°E., 126.7 ft.  
40" Pine, now burnt stob and hole, N.35°W., 105.0 ft

Set Brass cap at cor. mkd: County Surveyors Office  
R T 31 S R  
8 S 25 | S 30 7  
W S 36 | S 31 W  
1970

New BTs -16" D.Fir S.89°W., 22.1 ft. mkd. T31S R8W S36 CSBT  
14" D.Fir N.19°W., 22.5 ft. mkd. T31S R8W S25 CSBT  
13" D.Fir N.24°E., 22.4 ft. mkd. T31S R7W S30 CSBT  
16" D.Fir S.27°E., 17.6 ft. mkd. T31S R7W S31 CSBT

Fd. and used in BLM Resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors, under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO records Vol. 41 Page(s) 16187-88)

Fd. OK, Aug. 1981 by H. Johnstone - M 88-62

continued next page

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 36; & 30, 31 of T31-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM retracement by Brandon G. Courtright, Cadastral Surveyor, under Group No. 2500, Admin file No. 1407 - surveyed July 2014 - (DCSO records Plat 2015-1, T32S R7W and copy in Vol. 58 Page 23206)

-----  
The cor. of secs. 25, 30, 31, & 36, on the W. bdy. of the Tp., monumented with an iron post, 1½" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd. continued next page from which the remains of the original BTs

A burnt pine stump, size indeterminate, bears S.68°E., 80.5 ft., with no marks visible.

A burnt pine stump, 48" dia., bears S.63°W., 167.1 ft., with no marks visible. (Record, S.53½°W., 165.0 ft.) and the remains of the BTs mkd. by the Douglas County Surveyor's Office in 1970 reported by Jelley & Carlson in 1976-77 (Record, Byron)

A burnt fir snag, 16" dia., bears N.24°E., 22.4 ft., with a healed blaze.

A roothole bears S.27°E., 17.8 ft., with a fir trunk, 27" dia., lying alongside, with no marks visible.

A roothole bears N.19°W., 22.4 ft., with a burnt fir trunk, 22" dia., lying alongside, with a healed blaze. and new accessories

A rebar, 30" long, 5/8" dia., driven 22" in the ground for a reference monument, bears N.48°55'09" E., 18.17 ft., with an aluminum cap mkd. RM T31S R7W S30 18.17 FT TO COR 2014, and an arrow pointing to the cor.

A rebar, 30" long, 5/8" dia., driven 21" in the ground for a reference monument, bears S.52°38'00"E., 23.51 ft. dist., with an aluminum cap mkd. T31S R7W S31 23.51 FT TO COR 2014, and an arrow pointing to the cor.

Alongside the cor. is an aluminum fence post.

NAD 1983 (2011)

Latitude 42°50'23.14"N

Longitude 123°35'03.44"W.