

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19 of T31-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8031)

Set a Fir post, 3 ft. long, 3" dia., 18" in the ground marked ¼ S on W. side for the ¼ sec. cor., from which

A Fir 38" dia., bears N.80°E., 16 lks. dist. mkd. ¼ S BT.

A Fir 38" dia., bears S.82°W., 37 lks. dist. mkd. ¼ S BT.

Looked for, not found, by DCSO crew - July 1969 - C.S. File 54/36-21

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - March 8, 1977 - M 65-5

Set 5/8" x 40" Iron rod and alum. cap, from which

6" Fir bears N.81½°E., 27.7 ft.

20" Fir bears N.83°W., 32.8 ft.

Ron Quimby - Crew: J. Leonard and N. Fromdahl - 2/2014 - C.S. File 65/82-22

Found - 5/8" I.Rod with alum. cap (properly mkd)

14" D.Fir N.81°E., 27.7 ft. good scar.

24" Fir stump (6' tall) N.83°W., 32.8 ft. badly burnt.

New - 8" D.Fir S.14°E., 21.5 ft. scribed ¼ S19 BT.

7" D.Fir S.52dW., 39.8 ft. scribed ¼ S24 BT.

Compass decl. 15½°E.