

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18 of T31-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8032)

Set a Laurel post, 3 ft. long, 3" sq., 18" in the ground, for the ¼ sec.cor. marked ¼ S on W. side, from which

A Fir 18" dia., bears S.58°E., 70 lks. dist. mkd. ¼ S BT.

A Fir 16" dia., bears S.42°W., 28 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Cliff Stone - Dec. 1966 - C.S. File 54/36-65

Found - 16" now 36" D.Fir S.42°W., 18.5 ft. Some marks visible, I believe to be scribe marks. Also, notches in bark below face which is common to Byars' work.

18" D.Fir, now down and burnt, S.58°E., 46.2 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S

R8W ¼ S13|S18 R7W

1966

New BTs -7" Live Oak S.1°W., 20.2 ft. mkd. ¼ S13 CS BT.

9" Live Oak N.5°E., 6.0 ft. mkd. ¼ S18 CS BT.

Cor. Fd. and used in BLM Resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors, under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO records Vol. 41 Page(s) 16194)