

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW. Cor. Sec. 31 (Tps. Cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8173)

Set a stone 14x8x5 ins., 10" in the ground, mkd. with six notches on the E., W., and N. edges, for the cor. to Township 31 S Ranges 9 and 10 W., from which
A Laurel 5" dia., bears N.50°E., 48 lks. dist. mkd. T31S R9W S31 BT.
A Fir 5" dia., bears N.70°W., 180 lks. dist. mkd. T31S R10W S36 BT.

Survey by Arnold Gibson and Charles W. Cook, for: Oregon State Board of Forestry - July 20, 1972 - C.S. 55/233-15

Found - Orig. 14"x8"x5" basalt stone, now in place, no marks visible.
5" Laurel bears N.50°E., 48 lks.; clump of 4 in place, no marks visible.
5" Fir bears N.70°W., 180 lks.; now 22" in place, exposed scribe B.
Set 4" x 4" x 72" White painted Cedar post 2.0 ft. S.67°E., of corner stone, from which a:
13" Fir bears East 21.5 ft. to face; scribed T31S R9W S31 BT RS359.
18" Fir bears N.40½°W., 56.7 ft. to face; scribed T31S R9W S31 BT.
OSBF department metal location poster on 13" Fir BT, East 21.5 ft.