

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & 36, T31-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8174)

Set a basalt stone 22x14x6 ins., 15" in the ground, mkd. ¼ on W. face, for ¼ corner, from which
A Fir 8" dia., bears N.82°E., 36 lks. dist., mkd. S31 ¼ S BT.
A Fir 8" dia., bears N.63°W., 18 lks. dist. mkd. S36 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 6, 1967 - C.S. File 54/32-89

Found - Stone, no markings. (stone, 22x14x6, as recorded)
Orig. 8" now 18" D.Fir N.82°E., 23.8 ft., shows scar.
Orig. 8" now 30" D.Fir N.63°W., 11.9ft., opened and found scribe "S".

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S
¼
R10W S 36 | S 31 R9W
1967

Rescribe-18" D.Fir N.82°E., 23.8ft. (orig.) mkd. ¼ S31 CS BT
New BT - 14" D.Fir N.46½°W., 16.8 ft. mkd. ¼ S36 CS BT.
Cor. lies 43 ft. South of creek.