

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T31-10

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8174)

 Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for the cor. of secs. 25,30, 31 and 36, I mark T31S S30 on NE.; R9W S31 on SE.; R10W S36 on SW.; and S25 on NW. sides, with 5 notches on N. and 1 notch on S. angles, from which
 A Fir 10" dia., bears N.50°E., 313 lks.dist. mkd. T31S R9W S30 BT.
 A Fir 10" dia., bears S.45°E., 56 lks. dist. mkd. T31S R9W S31 BT.
 A Fir 8" dia., bears S.40°W., 182 lks. dist. mkd. T31S R10W S36 BT.
 A Fir 8" dia., bears N.77°W., 295 lks. dist. mkd. T31S R10W S25 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 1967 - C.S. File 54/32-75

 Found - 10" now 28" D.Fir, N.52½°E., (Rec. N.50°E.) 206.6 ft., shows good scar.
 10" now 28" D.Fir snag, S.45°E., 37.0 ft., opened earlier, "R9" visible.
 8" now 19" D.Fir, N.77°W., 194.7 ft., shows good scar.
 No trace of SW. BT.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 31 S	R
10	S 25 S 30	9
W	S 36 S 31	W

 1967

New BTs- 14" D.Fir N.63°E., 78.5 ft. mkd. T31SR9W S30 CSBT
 10" D.Fir S.67½°E., 51.1 ft. mkd. T31S R9W S31 CSBT
 17" Pine S.43°W., 18.7 ft. mkd. T31S R10W S36 CS BT

Fd. BC & BTs as per rec. 4/2015 by T. Hostetter M169-54