

PRIMARY CORNER DESCRIPTION 1/4 cor. for Sec. 31 & 6 T31-9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7383)

Set ¼ sec. post, from which
A Hemlock 12" dia., bears N.89°E., 26 lks. dist.
A Chinquapin 5" dia., bears S.20°E., 10 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7398-99)

I find 2 witness trees, each mkd. ¼ S BT. The post cor. is burned. At cor. point, I set a stone 12x12x8 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which
A Hemlock 12" dia., bears N.89°E., 26 lks. dist. mkd. ¼ S BT.
A Chinquapin 5" dia., bears S.20°E., 10 lks. dist. mkd. ¼ S BT.
These witness trees are both dead. I therefore mark two new witness trees.
A Hemlock 10" dia., bears N.57 ¾°W., 20½ lks. dist. mkd. ¼ S BT.
A Fir 15" dia., bears S.40 ¾°E., 30 lks. dist. mkd. ¼ S BT.

Tied corner in GLO survey by W.H. Byars, Deputy Surveyor under contract # 727 dated JDec. 20, 1900 (DCSO records Vol. 19 Page(s) 8237)

Survey by Forest LaFlamme - For: Georgia Pacific Corp. - Aug. 12, 1963 - C.S. File 51/265

Found - Orig. stone with the chisel marks faintly showing.
Orig. Fir 15", S.40 ¾°E. is now 30" dia. and is plainly scribed.
Orig. Hemlock BT is gone.
I scribe W.Cedar 9", N.22°W., 26.3 ft. "¼ S31 BT".

By computation it was determined that the ¼ corner was a common one by Randy Smith, Deputy Co. Surveyor 10/2/2009