TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8224)

A fir, 18" dia., mkd. S30 ¼ S on N & S31 ¼ S on S faces for the ¼ sec. corner from which
A fir, 36" dia., bears N.5°E., 30 lks., mkd: S30 ¼ S BT.
A fir, 14" dia., bears S.60°E., 12 lks., mkd: S31 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - May 1967 - C.S. File 54/32-83

Found - 18" corner tree, now 18" snag, scribe visible, "¼ S30" on N face, South face rotted.
36" D.Fir N.5°E., 23.2 ft. old face badly burnt (Rec. 19.8 ft.) found scribe marks not legible.
14" now 20" D.Fir S.60°E., 7.9 ft., shows good scar.
Set - Brass cap on S side of corner tree mkd: T31S R9W
COUNTY SURVEYORS OFFICE 1967 ¼ S 30 / S 31
New BT - 9" Laurel N.70°W., 12.0 ft. mkd. ¼ S30 CS BT.

Fd. BC & BTs as per rec. 4/2015 by T. Hostetter M169-54