

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8229-30)

Set a basalt stone, 14x14x12", 10" in the ground, marked ¼ on N face for the ¼ sec. cor. from which
A fir, 16" dia., bears N.28°E., 43 lks., mkd: S18 ¼ S BT.
A fir, 24" dia., bears S.20°W., 88 lks., mkd: S19 ¼ S BT.

Clifford A Stephens - For: Coos Head Timber Co - March 1959 - C.S. file 51/178 & M20-16

Intersect the ¼ Section corner
Find two BTs - No Rock - BT is recorded in the SW quadrant actually in SE quadrant.
Set pipe and White Cedar post for the Corner from which:
A Fir 26" in dia. brs. S.20°E., 58.1 ft (recorded as being in SW quadrant)
A Fir 24" in dia. brs. N.28°E., 28.4 ft (face opened for verification - found scribing)

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - May 1967 - C.S. File 54/32-76

Found - No trace of Iron Pipe set in 1961
Orig. 24" D.Fir, N.28°E., 28.4 ft., tree opened earlier, scribe narks visible.
26", now 26" D.Fir Snag, S.24°E., 58.1 ft., tree shows good scar.
Set - Brass Cap at Cor. mkd. County Surveyors Office T31S R9W
1967 ¼ S 18
S 19
New BT - 8" Cedar S.50°E., 14.0 ft. mkd. ¼ S19 CS BT.
Note - This corner lies about 250.0 ft. E. of Standly Creek.

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #1679, surveyed July-Oct. 1993 - (DCSO records Vol. 51 Page(s) 19563)

The ¼ sec. cor. of secs. 18 & 19, perpetuated and recorded by Stephens, in 1959-1961, subsequently perpetuated and recorded by the County Surveyor's Office in 1967, monumented with an iron post, 1½" dia, firmly set, projecting 16" above the ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A sawed fir stump, 36" dia, bears N.32°E., 41½ lks., with scribe mark S and other illegible marks visible on detached double blaze. (Record, N.28°E., 43 lks.) CONT.

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 26" dia, bears S.23¼°E., 85½ lks., with
healed double blaze. (Record, S.20°W., 88 lks.)
and new bearing trees
A fir, 6" dia, bears S.15¾°W., 32 lks., mkd. ¼ S19 BT.
A Port Orford cedar, 6" dia, bears N.79¼°W., 30½ lks.,
mkd. ¼ S18 BT.