TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8232)

Set a Basalt stone, 14x12x3", 10" in the ground, marked ¼ on N face for the ¼ Sec. cor. from which
A fir, 12" dia., bears N.30°E., 67 lks., mkd: S7 ¼ S BT.
A fir, 12" dia., bears S.80°W., 40 lks., mkd: S18 ¼ S BT.

C.S. Lehmanowsky, Engineer - April 20, 1959, Filed May 4, 1959 - C.S. File 51/18

Set - a 4" sq. post for this corner, from orig. BTs.
12" Fir S.80°W., 40 lks. is now a snag & unlikely to withstand logging operation.
The notes for the orig. 12" Fir N.30°E., 67 lks., should read Fir 12" N.12°E., 67 lks.
New BT - 36" Fir S.64°E., 19.0 ft. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - March 1967 - C.S. File 54/32-34

Found - 12" D.Fir, now stump, N.12°E., 44.2 ft., opened for scribe "BT"
36" D.Fir, now stump, S.64°E., 19.0 ft., scribe visible "BT" 1959
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1967 ¼ S 7 / S 18 T31S R9W
New BT - 12" Cedar S.84°W., 92.0 ft. mkd: ¼ S18 CS BT.
No other trees available.