

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8235)  
-----  
Set a conglomerate stone 14x13x3" 10" in the ground, marked 1/4 on N face for the 1/4 Sec. corner, from which  
A fir, 30" dia., bears N.12°E., 25 lks., mkd: S6 1/4 S BT.  
A fir, 36" dia., bears S.9°E., 22 lks., mkd: S7 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & D. West - Feb./March 1967 - C.S. File 54/32-27  
-----  
Found - 30" now 34" D.Fir, N.12°E., 14.5 ft. (record 16.5') shows good scars.  
36" D.Fir, now stump, S.9°E., 14.5 ft., open for scribe "S"  
Set - Brass cap at 1/4 cor. mkd: COUNTY SURVEYORS T31S R9W  
OFFICE 1/4 S 6  
1967 S 7  
New BT - 9" D.Fir S.33°W., 47.3 ft., 1/4 S7 CS BT.