

PRIMARY CORNER DESCRIPTION 1/4 cor for Secs. 6 & 31; T30-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page 7383)

-----  
Set ¼ sec. post, from which  
    A Hemlock 12" dia., bears N.89°E., 26 lks. dist.  
    A Chinquapin 5" dia., bears S.20°E., 10 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7398-99)

-----  
I find 2 witness trees, each mkd. ¼ S BT. The post cor. is burned. At cor. point, I set a stone 12x12x8 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which  
    A Hemlock 12" dia., bears N.89°E., 26 lks. mkd. ¼ S BT.  
    A Chinquapin 5" dia., bears S.20°E., 10 lks. mkd. ¼ S BT.  
These witness trees are both dead. I therefore mark two new witness trees.  
    A Hemlock 10" dia., bears N.57¾°W., 20½ lks. mkd. ¼ S BT.  
    A Fir 15" dia., bears S.40¾°E., 30 lks. mkd. ¼ S BT.

Tied corner in GLO survey by W.H. Byars, Deputy Surveyor under contract # 727 dated Dec. 20, 1900 (DCSO records Vol. 19 Page(s) 8237)

Survey by Forest LaFlamme - For: Georgia Pacific Corp. - Aug. 12, 1963 - C.S. File 51/265

-----  
Found - Orig. stone with the chisel marks faintly showing.  
    Orig. Fir 15", S.40 3/4°E. is now 30" dia. and is plainly scribed.  
    Orig. Hemlock BT is gone.  
I scribe W.Cedar 9", N.22°W., 26.3 ft. "¼ S31 BT".

By computation it was determined that the ¼ corner was a common one by Randy Smith, Deputy Co. Surveyor 10/2/2009

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 10/5/2009 - C.S. File 67/28-37

-----  
Condition report only  
Found - 12x10x6" (rec. 12x12x8") 1893, stone loose out of ground marked "¼" on side. Stone is found along southerly edge of metal fence post with attached tag. Fence post protrudes 15" out of ground, source of fence post unknown.

continued next page

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 cor for Secs. 6 & 31; T30-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From fence post

15" now 34" dia., 40' tall D.Fir snag. Previously opened no marks visible bears S.40 $\frac{3}{4}$ °E., 19.8 ft. Agrees w/rec. 1893

9" now 18" dia., W.Cedar with a fully healed blaze bears N.22°W., 25.0 ft rec. N.22°W. 26.3 ft. 1963

13" hemlock with a partially healed single blaze scribing visible "S6 BT" bears S.62°W., 14.3 ft. rec. per tag. S.65°W., 14.3 ft. tagged by LaFlamme, BT not of record in Douglas Co.

10" W.Cedar with a single unhealed blaze scribing visible "T30 R9  $\frac{1}{4}$  S31 BT" bears N.48°E., 8.7 ft. to center of root crown, 10.0 ft to center of trunk. BT tag dated 12/07 by CH "N.48°E., 10.6 ft. BT not of record in Douglas County

Note - Corner lies 15 ft. easterly of N'ly-S'ly cut line. Compass decl. 16 $\frac{1}{4}$ °E.