

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8222)

Set a basalt stone, 12x12x6" 8" in the ground marked ¼ on W face for the ¼ sec. cor. from which
A laurel, 12" dia., bears N.35°E., 33 lks. mkd: S32 ¼ S BT
A fir, 6" dia., bears N.82°W., 49 lks., mkd: S 31 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - April 3, 1967 - C.S. File 54/32-58

Found - 12" now 13" Laurel, N.35°E., 21.8 ft., face rotten.
6" now 10" D.Fir N.82°W., 32.3 ft., opened for scribe "BT"
No trace of corner stone.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T31S R9W
OFFICE 1967 ¼ S 31|S 32
New BTs- 12" Live Oak N.32°W., 27.6 ft. mkd. ¼ S31 CS BT.
12" Laurel N.34°E., 26.0 ft. mkd. ¼ S32 CS BT.
Note - This corner lies approx. 260.0 ft. north of small creek on Steep S. slope.