TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8225)

Set a basalt stone, 20x15x5", 15" in the ground, marked ¼ on W side for the ¼ sec. cor. from which
A Fir, 30" dia., bears East, 19 lks., mkd: S29 ¼ S BT
A fir, 40" dia., bears S.50°W., 44 lks., mkd: S30 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - March 1967 - C.S. File 54/32-59

Found - Stone at ¼ corner, right size, but no marks visible.
30" D.Fir, now 32" snag, East 12.5 ft., opened for scribe "¼"
40" now 43" D.Fir, S.45°W., (Rec. S.50°W.) 29.0 ft. shows good scar.
Set Brass cap at cor. mkd: COUNTY SURVEYORS T31S R9W
OFFICE 1967 ¼ S 30|S 29
New BT - 30" D.Fir N.16°E., 8.9 ft. mkd: ¼ S29 CS BT.

Fd. BC & BTs as per rec. 4/2015 by T. Hostetter M169-54