

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8225)

Mark a pine, 8" dia., T31S S20 on the NE, R9W S29 on the SE, S30 on the SW & S19 on the NW faces & 2 notches on the S & 5 notches on the E edges for the cor. of Secs. 19, 20, 29, & 30, from which

- A pine, 10" dia., bears N.80°E., 68 lks., mkd: T31S R9W S20 BT.
- A pine, 8" dia., bears S.75°E., 13 lks., mkd: T31S R9W S29 BT.
- A pine, 5" dia., bears S.45°W., 2 lks., mkd: T31S R9W S30 BT.
- A pine, 5" dia., bears N.60°W., 78 lks., mkd: T31S R9W S19 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - May 1967 - C.S. File 54/32-87

Found - 8" Pine, now 9" snag, shows scribing "S19 S20 S29".
 10" pine, now 10 stob, N.80°E., 44.8 ft. shows scribing "BT"
 8" now 12" pine, S.75°E., 8.6 ft. shows scribing.
 5" now 10" pine, S.45°W., 1.3 ft. shows scribing "3"
 5" now 10" pine N.60°W. 51.5 ft shows scribing "S19"

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T31S R9W
 OFFICE S 19 | S 20
 1967 S 30 | S 29

New BT - 10" D.Fir N.3°E., 15.2 ft. mkd. T31S R9W S20 CS BT.

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #1679, surveyed July-Oct. 1993 - (DCSO records Vol. 51 Page(s) 19558)

The cor. of secs. 19, 20, 29, and 30, perpetuated and recorded by the County Surveyor's Office in 1967, monumented with the sawed pine stump of the original corner tree, 8" dia., with illegible scribe marks visible on partially healed NE. blaze, from which the remains of the original BTs:

- A broken off pine snag, size indeterminate, bears N.80°E., 68 lks., with illegible scribe marks visible on decomposed blaze.
- A broken off pine snag, 12" dia., bears S.75°E., 13 lks., with scribe marks 29 31S R9W visible on partially healed blaze.
- A pine snag, 10" dia., bears S.45°W., 2 lks., with illegible scribe marks visible on partially healed blaze.

continued next page

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole, bears N.60°W., 72 lks., alongside of which is an uprooted pine, 10" dia., no marks visible. (Record, 78 lks.)
and the monument and BT mkd. by the County Surveyor's Office
An iron post, 1½ ins. diam., firmly set, projecting 7" above the ground, bears N.65°E., 1 lk., with brass cap mkd. COUNTY SURVEYORS OFFICE T31S R9W S19 S20 S30 S29 1967 and a +.
A fir, 16" dia., bears N.6°E., 22½ lks. with healed blaze.
and new bearing trees
A live oak, 6" dia., bears S.27°E., 57½ lks., mkd. T31S R9W S29 BT.
A live oak, 7" dia., bears S.64½°W., 119½ lks., mkd. T31S R9W S30 BT.
A fir, 10" dia. bears N.5°W., 37½ lks. mkd T31S R9W S19 BT