TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8228)

Marked a fir, 6" dia., S20 ¼ S on E & S19 ¼ S on W faces for the ¼ Sec. cor. from which

A live Oak, 8" dia., bears N.55°E., 20 lks., mkd: S20 ¼ S BT.

A live oak, 8" dia., bears N.45°W., 12 lks., mkd: S19 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - March/April 1967 - C.S. File 54/32-57

Found - 6" D.Fir corner tree, now 12", shows good scar.
8 L.O. now 9", N.45°W., 7.9 ft. scribe visible "S19 ¼"

Set - Brass cap on N edge of corner tree mkd:
COUNTY SURVEYORS T31S R9W
OFFICE 1967 ¼ S19|S 20

New BTs- 27" D.Fir S.42°E., 21.6 ft. mkd. ¼ S20 CS BT.

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #1679, surveyed July-Oct. 1993 - (DCSO records Vol. 51 Page(s) 19561)

The ¼ sec. cor. of secs. 19 and 20, perpetuated and recorded by the Douglas County Surveyor's Office in 1967, monumented with the original corner tree, a fir, 17" dia., with healed blazes on E. & W. sides, from which the remains of an original BT:

A live oak snag, 9" dia, bears N.45°W., 12 lks., with illegible scribe marks on partially healed blaze.

and RM & BT mkd. by the County Surveyor's Office

An iron post, 1½" dia, bears North, 2 lks., firmly set, projecting 12 above the ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T31S R9W ¼ S19 S20 1967 and a vertical line in the center.

A fir, 32" dia, bears S.44¼°E., 31 lks., with healed double blaze.

and a new bearing tree

A live oak, 7" dia, bears N.13°W., 61½ lks., mkd. ¼ S19 BT