

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs 17, 18, 19, & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8228)

Set a fir post 4 ft. long, 4" sq. 24" in the ground, for cor. to Secs. 17, 18, 19 & 20 and marked T31S S17 on NE, R9W S20 on SE, S19 on the SW & S18 on the NW faces, with 3 notches on the S and 5 notches on the E edges, from which
A fir, 36" dia. bears N.70°E. 34 lks. mkd: T31S R9W S17 BT
A fir, 16" dia. bears S.32°E. 57 lks. mkd: T31S R9W S19 BT
A fir, 16" dia. bears S.35°W. 58 lks. mkd: T31S R9W S20 BT
A cedar, 24" dia., bears N.60°W., 57 lks., mkd: T31S R9W S18 BT.

Clifford A Stephens - For: Coos Head Timber Co - 3/18/1959 - C.S. file 51/178 & M20-16

Find BTs in good condition and set ½" iron pipe and post for the corner from which:
A Fir 38" in dia. brs. N.70°E., 23.3 ft
A Fir 18" in dia. brs. S.38°E., 37.7 ft
A Fir 20" in dia. brs. S.30°W., 36.6 ft
A Port Orford Cedar 24" in dia. brs. N.59½°W., 37.0 (Scribing visible)
All original BTs - None opened - (Scar of face visible).

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - March 1967 - C.S. File 54/32-29

Found - ½" iron pipe. 1959
Orig. 38" Fir, now stump, N.70°E., 23.3 ft. shows good scar.
Orig. 18" Fir, down, S.38°E., 37.6 ft., shows good scar.
Orig. 20" Fir, now 29" S.30°W., 36.6 ft., shows good scar.
Orig. 24" Port Orford Cedar, now stump, N.59½°W., 37.0 ft., shows scribing "S18 T31S R9W BT"
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T31S R9W
OFFICE S 18 | S 17
1967 S 19 | S 20
New BTs- 36" Cedar S.1°E., 20.4 ft. mkd. T31S R9W S20 CS BT.

Jack E. LaFlamme, LS 378 - For: Georgia Pacific - March 1990 - C.S. File 63/104-7

Found - I find a ½" iron pipe set by Clifford Stephens at the cor. of secs. 17, 18, 19, & 20.
continued next page

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor Secs 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

I also find the 1967 BLM brass cap (Rec. is 1967 County BT) lying on the ground nearby so I lay it against the ½" pipe.
The orig. 36" Fir BT, N.70°E., 34 lks is now a 48" stump with face grown over.
The Orig. 16" Fir BT, S.32°W., 57 lks., is now a 26" with face grown over.
New - I chop an "X" on the stump of the orig. 24" Cedar BT, N.60°W., 57 lks.
I scribe "S20 BT" 278" on a 16" Fir, S.37°15'E., 31.5 ft. to the center.

BLM dependent resurvey by Francis J. Simon, Cadastral Surveyor under Group #1679, surveyed July-Oct. 1993 - (DCSO records Vol. 51 Page(s) 19561-2)

The cor. of secs. 17, 18, 19, & 20, perpetuated & recorded by Stephens, in 1959-1961, subsequently perpetuated and recorded by the County Surveyor's Office in 1967, and subsequently perpetuated and recorded by LaFlamme, in 1990, monumented with an iron pipe, ½" dia., firmly set, projecting 5" above the ground, alongside of which is lying an iron post, 1½" dia, 30 ins. long, with brass cap mkd. as described in the county record, from which the remains of the orig. BTs:

- A fir stump, 46" dia, bears N.70°E., 34 lks., with healed blaze.
- A root hole, bears S.35°E., 58 lks., alongside of which is an uprooted fir, size indeterminate, no marks visible.
- A fir, 32" dia, bears S.30°W., 57 lks., with healed blaze. (Record, S.32°W.)
- A cedar stump, 24" dia, bears N.60°W., 57 lks., with axe mark X.

and remains of the BT mkd. by the County Surveyor's Office

- A root hole, bears S.1°E., 31 lks., alongside of which is an uprooted cedar, 36" dia, with scribe marks T31S R9W S20 CS BT visible on partially healed blaze.

and a bearing tree mkd. by LaFlamme

- A fir, 14" dia, bears S.38°E., 48½ lks., with healed blaze

At the corner point
Reset the Douglas County Surveyor's iron post, 25" in the ground, directly over the iron pipe, with brass cap (properly) mkd.
from which new bearing trees

- A fir, 8" dia, bears N.63¾°E. 36 lks. mkd. T31S R9W S17 BT
- A fir, 7" dia, bears N.24°W. 24½ lks. mkd. T31S R9W S18 BT

continued next page

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, control station EC41188, established by the Control Survey Unit of the Oregon State Office, BLM, in 1993, at Latitude 42°52'18.77189"N. & Longitude 123°48'04.33603"W. (NAD 1927), bears N.28°35'27"W., 24.539 chs. (mean bearing and sea level distance); monumented with an aluminum cap, 3" dia, set flush with the ground, mkd. EC41188 GPS 1993. The geographic position (NAD 1927) of the corner of sections 17, 18, 19, & 20, determined by a tie to control station EC41188, established by the Geodetic Control Unit of the Oregon State Office, BLM, in 1993, is as follows:
Latitude: 42°52'04.73"N. Longitude: 123°47'53.93" W.
NAD 1927
The mean magnetic declination is 18° East.