TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8230)

Marked a fir, 36" dia., S17 ¼S on E & S18 ¼S on W faces for the ¼ sec. cor. from which
A fir, 12" dia., bears S.55°E., 34 lks., mkd: S17 ¼ S BT.
A fir, 20" dia., bears S.12°W., 40 lks., mkd: S18 ¼ S BT.

Clifford A Stephens - For: Coos Head Timber Co - March 1959 - C.S. file 51/178 & M20-16

Set iron pipe on the South Side of a 36" Fir which was originally marked for the 1/4 Section Corner. Face on E and W side of tree from which:
A Fir 22" in dia. brs. S.54°E., 22.3 ft.
A Fir 18" in dia. brs. S.12½°W., 28.0 ft
(original BTs)

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - March 1967 - C.S. File 54/32-51

Found - 1½" Iron Pipe & Corner Tree
Orig. 22" D.Fir, now Stump, S.54°E. 22.3 ft., scribe visible "¼ S"
No trace of SW Bearing tree
Set - Brass Cap alongside I.P. on S Side of corner tree, mkd:
COUNTY SURVEYORS T31S R9W
OFFICE 1967 ¼ S 18|S 17
New BTs- 12" Hemlock S.83°E., 73.0 ft. mkd. ¼ S17 CS BT.
10" W.Fir N.32°W., 45.0 ft. mkd. ¼ S18 CS BT.