TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8230-1)

Set a Fir post, 4 ft. long, 4" sq., 24 in the ground for corner to Secs. 7, 8, 17 and 18, marked T31S S8 on NE, R9W S17 on SE, S18 on the SW and S7 on the NW faces, with 4 notches on the S and 5 notches on the E edges, from which

A fir, 18" dia. bears N.70°E., 32 lks. mkd: T31S R9W S8 BT
A fir, 24" dia. bears S.30°E. 51 lks. mkd: T31S R9W S17 BT
A fir, 48" dia. bears S.75°W. 64 lks. mkd: T31S R9W S18 BT
A fir, 20" dia. bears N.48°W., 30 lks. mkd: T31S R9W S7 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - March 1967 - C.S. File 54/32-30

Found - Orig. 18" Fir, now Stump, N.70°E., 21.1 ft. fd scribe "B"
Orig. 24" Fir, now stump, S.30°E., 33.7 ft., shows good scar
Orig. 48" Fir, now Stump, S.75°W., 42.2 ft., shows good scar
Orig. 20" Fir, now Stump, N.48°W. 19.8 ft., shows good scar

Note - Then are no other trees in range for scribing.

Set- Brass Cap at Cor. mkd: County Surveyors Office 1967

T31S	R9W
S 7	S 8
S 18	S 17