TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8233)

Set a basalt stone 18x12x6", 12" in the ground, marked with 5 notches on S & E edges for the cor. of secs. 5, 6, 7, & 8, from which

A cedar, 12" dia., bears N.25°E., 96 lks., mkd: T31S R9W S5 BT.
A cedar, 8" dia. bears S.48°E. 59 lks. mkd: T31S R9W S8 BT
A fir, 48" dia., bears S.45°W., 5 lks. mkd: T31S R9W S7 BT
A fir, 48" dia. bears N.30°W., 23 lks. mkd: T31S R9W S6 BT

Clifford A. Stephens - For: Coos Head Timber Co. - Jan. 1959 - C.S. File 51/178 & M20-16

Find BTs & set ¾" iron pipe & post from which

A cedar 18" in dia., brs. S.46°E., 41.5 ft.
A cedar 26" in dia., brs. N.79°E., 57.3 ft., (Not recorded in orig. notes)
A fir 48" in dia., brs. S.45°W., 3.3 ft. (now a snag)
A fir 30" in dia., brs. N.30°W., 8.6 ft.
A cedar 12" in dia., brs. N.25°E., 63.3 ft. (down)

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & D. West - Feb./March 1967 - C.S. File 54/32-28

Found - Did not find ¾" iron pipe as recorded 1959
18" cedar, now down & burned, S.46°E., 41.5 ft., scribe visible, "T31S R9W"
48" D.Fir now burnt snag, S.45°W., 3.3 ft.
30" D.Fir now burnt snag, N.30°W., 8.6 ft.

Set - brass cap at cor. mkd: COUNTY SURVEYORS T31S R9W
OFFICE
1967

S 6 | S 5
S 7 | S 8

New BTs- 7" hemlock N.46°W., 70.3 ft. mkd. T31S R9W S6 CS BT.
24" cedar stump S.58°E., 49.8 ft.

Note - No other tree available. Tagged old trees.