

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8236)

Marked a fir, 18" dia., S5 ¼ S on E & S 6 ¼ S on W faces for the ¼ sec. corner from which

A fir, 16" dia., bears N.78°E., 11 lks., mkd: S5 ¼ S BT.

A fir, 18" dia., bears N.32°W., 63 lks., mkd: S6 ¼ S BT.

Clifford A. Stephens - For: Coos Head Timber Co. - Jan. 1959 - C.S. File 51/178 & M20-16

Find the fir marked for the ¼ section corner from which:

18" Fir bears N.61°E., 5.5 ft.

A Fir snag 18" in dia., bears N.34°W., 42.0 ft.

Forest J. LaFlamme - For: Georgia Pacific Corp. - Aug. 12, 1963 - C.S. File 51/265

Found - The orig. 18" fir BT N.32°W., 41.5 ft., now a snag. The fir for the corner & other Orig. BTs are now uproots.

From the orig. BT standing in place, I set a 1¼" pipe for the ¼ Corner & scribe: 22" D.Fir S.27°E., 57.4 ft., "¼ S5 BT"

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - May 1967 - C.S. File 54/32-80

Found - I. Pipe at ¼ corner. 1959
18" Fir, now 20" stump, N.32°W., 41.5 ft., shows good scar.

22" D.Fir, now stump, S.27°E., 57.4 ft., scribe visible, ¼ S5 BT.

Set Brass cap alongside I.Pipe mkd: COUNTY SURVEYORS T31S R9W OFFICE 1967 ¼ S6|S5

New BTs- 8" Hemlock S.78°W., 50.5 ft., mkd: ¼ S6 CS BT.

10" Cedar N.7°W., 57.3 ft., mkd: ¼ S6 CS BT.

No trees in Sec. 5.