

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8172)

Set a basalt stone 20x14x4 ins., 15" in the ground, mkd. ¼ on N. face for the ¼ sec. cor. of sec. 32, from which
A Fir 14" dia., bears N.30°E., 167 lks. dist. mkd. S32 ¼ S BT.
A Fir 48" dia., bears S.70°E., 74 lks. dist. mkd. S32 ¼ S BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12194)

Intersect at the ¼ sec. cor., which is a basalt stone, 20x14x4 ins., loosely set, mkd. and witnessed as described by the surveyor general. I perpetuate this cor., as follows:
Alongside the old cor.
Set an iron post 3 ft. long, 1" dia., 26" in the ground, for ¼ cor. of sec. 32, with brass cap mkd. $\frac{1}{4} S 32$
1917
from which
A Fir 18" dia., bears N.27°E., 166 lks. dist. mkd. ¼ S32 BT. (Old BT)
A Laurel 5" dia., bears N.2°W., 33 lks. dist. mkd. ¼ S32 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - May 1967 - C.S. File 54/32-85

Found - GLO brass cap, properly mkd. in 1917.
Orig. 38" D.Fir S.78°E., (48° face) shows good scars.
18" D.Fir now 29" stump, N.27°E., 109.6 ft., opened for scribe "3". Tree recently logged, opened log.
New BTs- 12" Pine N.12°W., 22.3 ft. mkd. ¼ S32 CS BT.
13" Pine N.52°E., 69.3 ft. mkd. ¼ S32 CS BT.
Corner lies on top ridge, running approx. N.20½°E-S20°W