

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Secs 5 & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8234)  
-----  
Set a basalt stone, 14x12x10" 10" in the ground, marked ¼ on N face for ¼ sec. corner, from which  
A hemlock, 18" dia., bears N.25°E., 40 lks. mkd: S5 ¼ S BT  
A hemlock, 9" dia., bears S.15°E., 9 lks., mkd: S8 ¼ S BT.

Clifford A. Stephens - For: Coos Head Timber Co. - Jan. 1959 - C.S. File 51/178 & M20-16  
-----  
Find mound of stone and the stone marked 1/4.  
Set new post in mound from which:  
A Hemlock 18" in Dia. brs. N.25°E., 26.4 Ft (gone)  
A Hemlock 16" in Dia. brs. S.15°E., 6.9 Ft  
New BT - A Fir 21" in Dia. brs. N.33°E., 49,7 Feet (Scribed)

Forest J. LaFlamme - For: Georgia Pacific Corp. - Dec. 2, 1966 - C.S. File 55/23  
-----  
Found - Orig. BT., now a snag.  
New BTs- Port Orford Cedar stump 27", S.44½°W., 30.3 ft., measured to the face "¼ S8 BT"  
Port Orford Cedar stump 30", N.42°E., 57.7 ft., measured to the face "¼S 5 BT"

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - April 1967 - C.S. File 54/32-26  
-----  
Found - 21" Fir, now burnt stump, N.33°E., 49.7 ft.  
16" Hemlock, now burnt snag, S.15°E., 6.9 ft., shows scar.  
LaFlamme's BTs:  
27" Cedar Stump S.44½°W., 30.3 ft., mkd: ¼ S8 BT.  
30" Cedar Stump N.42°E., 57.7 ft., mkd: ¼ S5 BT.  
(Dist. taken to face of stump which are painted red & tagged)  
Set Brass cap in mound of stone mkd:  
COUNTY SURVEYORS T31S R9W  
OFFICE ¼ S 5  
1967 S 8  
No trees in area to scribe.