

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32, T30-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7383)

-----  
Set ¼ sec. post, from which  
A Fir 18" dia., bears S.5°E., 10 lks. dist.  
A Fir 20" dia., bears N.73°E., 10 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #613, dated April 29, 1893 (DCSO records Vol. 17 Page(s) 7400)

-----  
This ¼ sec. cor. is burned. I find the witness trees. At Cor. point, I set a stone 14x10x4 ins., 9" in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which  
A Fir 18" dia., bears S.5°E., 10 lks. dist. mkd. ¼ S BT  
A Fir 20" dia., bears N.73°E., 10 lks. dist. mkd. ¼ S BT.  
These trees are both dead, I therefore mark 2 new witness trees:  
A Fir 18" dia., bears S.33 3/4°E., 26½ lks. dist. mkd. ¼ S BT.  
A Fir 30" dia., bears N.14¼°W., 128 lks. dist. mkd. ¼ S BT.

Survey by F.J. LaFlamme - For: Georgia Pacific - Dec. 2, 1966 - C.S. File 55/23

-----  
Found Original stone and 2 orig. BTs, now snags.  
Scribe 2 BTs for this corner:  
D.Fir 22", S.12°W., 34.7 ft. "¼ S5 BT 473"  
D.Fir 22" N.25°E., 13.5 ft. "¼ S32 BT"

Douglas Co. Surveyors Office - John M. Powell, and crew - May 16, 1967 - C.S. File 53/53-39

-----  
Found - Orig. 24" D.Fir now snag, S.37°E., 17.8 ft., scribe visible.  
24" D.Fir S.10°E., 34.0 ft. mkd. ¼ S5 BT.  
24" D.Fir N.26°W., 13.5 ft. mkd. ¼ S32 BT.  
Post at ¼ corner. Tagged all BTs by LaFlamme in 1966  
Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 9 W  
¼  $\frac{S\ 32}{S\ 5}$   
T 31 S R 9 W  
1967

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Stephen J. Flause, Deputy -  
Wit: T. Plouff; K. Mosley - April 7, 1981 - C.S. 61/19-32

-----  
Found - 1967 DCSO brass cap, properly mkd., on a 1" I.P.  
firmly set and protruding 6" from ground.  
1893 stone, measuring 14"x10"x4" is deposited on top  
of ground and set on the E. side of the brass  
cap. Stone is mkd. ¼ on its top side. (Rec. ¼ on  
N. face)  
A steel fence post protrudes 36" from the ground on  
the W. side of the brass cap monument.  
Possible remains of orig. SE. 18" Fir are found near  
record brg. & dist.  
No evidence of the other orig. BT is found.  
1893, A Fir 18" is now a burned D.Fir snag 18" DBH,  
approx. 35 ft. tall, bears S.34°E., 17.5 ft.,  
face measurement (Rec. S.33 3/4°E., 17.5 ft.)  
Tree has good evidence of burned blazes. No  
scribing visible.  
1893, A Fir 30" now the remains of a large burned  
and rotted Fir stump, bears N.14¼°W., 84.5 ft.  
No blazes or scribing apparent, rotted away.  
A D.Fir 22" now a dead 26" DBH D.Fir, bears S.10°W.,  
34.7 ft. (Rec. S.12°W., 34.7 ft.) Tree has burned  
open blaze with no legible scribing. (1966)  
A D.Fir 22" now a 38" DBH D.Fir, dead, bears  
N.25°E., 13.5 ft. An opened blaze has the  
scribing ¼ S32 visible. (1966)

Monument is accepted as found.

New Accessories:

- A boat spike in a 12" dia 12" tall burl'd Fir stump,  
bears N.06 3/4°W., 9.3 ft. Boat spike driven into  
the top of said stump is stamped BO 2.
- A spike in a D.Fir stump 20" dia and 21" tall, bears  
S.59½°W., 42.1 ft. Spike is stamped BO 1.
- An 8" DBH Madrone bears N.16°W., 81.9 ft. and is  
bark scribed ¼ S32 CS BT.

All accessories are tagged with DCSO BT tags.

Fd. OK, Sept. 23, 1992 by DCSO - C.S. File 64/32-6