

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 261100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 5 only, T32-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12193)

Set an Iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 cor. of sec. 5 only, with brass cap mkd.

1/4 S 5
1917

from which

A Laurel 20" dia., bears S.58°E., 17 lks. dist. mkd. 1/4 S5 BT.

A Fir 40" dia., bears S.46°W., 33 lks. dist. mkd. 1/4 S5 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - March/April 1967 - C.S. File 54/32-53

Found - 1917 GL0 brass cap, properly marked.
20" Laurel now 21", S.58°E., 11.2 ft., rotted face "1/4" visible.
40" now 42" D.Fir S.46°W., 21.8 ft., shows good scar.

New BT - 10" D.Fir S.37°E., 15.0 ft. mkd. 1/4 S5 CS BT.