

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 266100

PRIMARY CORNER DESCRIPTION A P on S. Bdy. Sec 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records C.S. File 64/76-2)

Set a Cedar post 3 ft. long, 3" sq., 20" in the ground for the ¼ sec. cor. mkd. ¼ S on N. side and from which
A Laurel 10" dia., bears S.10°W., 19 lks. dist. mkd. ¼ S BT.
A Yew 6" dia., bears N.25°W., 23 lks. dist. mkd. ¼ S BT.

GL0 survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8172)

Old ¼ sec. cor. Corner and witness trees standing.

GL0 Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12193)

Intersect at the old ¼ cor. of sec. 5, which is a decayed post, lying on the ground, witnessed as described by the surveyor general, the NW. BT being now dead. I change this cor. to an angle point and perpetuate it as follows: at the exact cor. point
Set an iron post 3 ft. long, 1" dia., 26" in the ground, for angle point, with brass cap mkd: AP
1917
from which
A Cedar 10" dia., bears N.43°E., 52 lks. dist. mkd. AP BT. (New BT)
A Laurel 12" dia., bears S.17°W., 19 lks. dist. mkd. AP BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - March/April 1967 - C.S. File 54/32-54

Found - Brass cap out of ground, mkd. by GL0 in 1917.
12" now 14" Laurel, S.17°W., 12.5 ft., tree rotten but found scribe marks, try to count rings but too fine.
No trace of NE. BT.
Reset Brass cap which falls in skid road.
New BTs- 8" Cedar S.61°E., 46.4 ft. mkd. AP CS BT.
25" Pine S.25°W., 34.6 ft. mkd. AP CS BT.
This A.P. cor. is 4.8 chs. East of N. ¼ cor. Sec. 5, T32-9