TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8212)

Set a basalt stone, 20x10x5", 14" in ground, marked ¼ on W side for the ¼ sec. cor. from which
A fir, 36" dia., bears S.52°E., 27 lks., mkd: S33 ¼ S BT.
A fir, 18" dia., bears N.85°W., 94 lks., mkd: S32 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - March 16, 1967 - C.S. File 54/32-40

Found - No trace of stone at ¼ corner.
Orig. 36" now 42" D.Fir S.52°E., 17.8 ft. opened for scribe "S"
Orig. 18" now 29" D.Fir N.85°W., 62.0 ft. shows good scar. I find this bearing to be N.75°W.
All BTs in good shape.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1967 ¼ S 32|S 33