

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8212)

-----  
Set a stone 12x10x6", 8" in the ground for cor. of secs. 28, 29, 32, & 33 mkd with 1 notch on S & 4 notches on E edges, from which

A Live Oak, 5" dia., bears N.82°E., 47 lks., mkd: T31S R9W S28 BT.

A Live Oak, 10" dia., bears S.65°E., 53 lks., mkd: T31S R9W S33 BT.

A Fir, 24" dia. bears S.10°W. 21 lks. mkd: T31S R9W S32 BT

A Fir, 6" dia. bears N.18°W., 92 lks. mkd: T31S R9W S32 BT

-----  
Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - March & April 1967 - C.S. File 54/32-64

-----  
Found - No trace of corner stone.  
28" D.Fir S.20°W., 13.9 ft. shows 2 good faces.  
10" Live Oak, now 11", S.65°E., 35.0 ft., shows scribing.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T31S R9W  
OFFICE S 29 | S 28  
1967 S 32 | S 33

Rescribed- 10" Live Oak, now 11" S.65°E., 35.0 ft. scribed "T31S R9W S33 CS BT"

New BTs- 36" D.Fir N.4°W., 40.4 ft. mkd: T31S R9W S28 CS BT.

26" D.Fir N.75°W., 30.0 ft. mkd: T31S R9W S28 CS BT.

-----  
Fd. BC; BTs down or dead: 11/1989, G. Riley; C.S. File 63/61

-----  
Douglas County Surveyors Office - Randall Smith - Stephen Flause - April 3, 1990 - C.S. 64/6-13

-----  
Found - 1967 2½" dia. DCSO brass cap on a 1¼" O.D. iron pipe protruding 7" above ground. 1967

24" now 28" dia. tipped out and laying on blaze. D.Fir bears S.10°W., 13.9 ft. to root hole (agrees with rec.) Orig. BT

10" now 11" dia. live Oak with scribing visible on an unhealed double blaze TT31S R9 S11 CS BT" bears S.65°E., 32.7 ft. (Rec. S.65°E., 35.0 ft. distance is a slope measurement.

No other original BTs found.

36" now 36" dia. 8 ft. high D.Fir snag with scribing visible on an unhealed single blaze, "T31S R9W S29 CS BT" bears N.4°W., 40.4 ft. (agrees with rec.) 1967

continued next page

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

26" now 31" dia. standing dead D.Fir with scribing visible on an unhealed double blaze "T31S R9W S28 CS BT" bears N.76°E., 30.0 ft. (agrees with BT tag, Renewal records is N.75°W., 30.0 ft.) 1967

New BTs- 28" dia. D.Fir double blazed and scribed "T31S R9W S33 CS BT" bears S.26¼°E., 39.3 ft.

17" dia. D.Fir double blazed and scribed "T31S R9W S33 CS BT" bears S.2¼°E., 60.3 ft.

3" dia. pistol butt D.Fir double blazed and scribed "X BT" bears N.33½°W., 65.8 ft. to center of trunk at upper blaze height (center of root crown difficult to determine).