

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8217)</p> <p>-----</p> <p>Set a cedar post, 4 ft. long, 4" sq. 24" in ground, mkd S16 ¼ S on E & S17 ¼ S on W faces for the ¼ sec. cor. from which</p> <p> A chinquapin, 8" dia., bears N.15°E., 25 lks., mkd: S16 ¼ S BT.</p> <p> A chinquapin, 6" dia., bears N.70°W., 49 lks., mkd: S17 ¼ S BT.</p>
<p>Clifford A. Stephens - For: Coos Head Timber Co. - Dec. 1959/Feb. 1961 - C.S. File 51/178 & M20-16</p> <p>-----</p> <p>No trace of orig. fd. BTs were chinquapin</p> <p>Set squared post & pipe for corner from which</p> <p> 36" Fir bears N.76°E., 18.3 ft.</p> <p> 12" Fir bears N.5°E., 27.3 ft.</p>
<p>Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - May 1967 - C.S. File 54/32-79</p> <p>-----</p> <p>Found - No trace of Iron Pipe, this area being heavily, logged.</p> <p> 36" D.Fir, now 36" Stump, N.76°E. 18.3 ft., badly burnt face, no good scribe left, faint "BT"</p> <p> 12", Now 14" D.Fir N.5°E., 27.3 ft., scribe visible "BT ¼"</p> <p>Set - Brass Cap at Cor. mkd: County Surveyors T31S R9W Office, 1967 ¼ S 17 S 16</p> <p>New BT - 13" Hemlock S.54°W. 73.8 ft. mkd. ¼ S17 CS BT.</p>
<p> </p>