

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8217-8)  
-----  
Marked a cedar 5" dia., T31S S9 on NE, R9W S16 on SE, S17 on SW & S8 on NW faces, with 4 notches on the S & E sides, the cor. of secs. 8, 9, 16, & 17, from which  
A fir, 24" dia. bears N.42°E., 10 lks. mkd: T31S R9W S9 BT  
A fir, 24" dia. bears S.40°E. 56 lks. mkd: T31S R9W S16 BT  
A fir, 10" dia. bears S.45°W. 36 lks. mkd: T31S R9W S17 BT  
A fir, 18" dia. bears N.65°W., 35 lks. mkd: T31S R9W S8 BT

Clifford A. Stephens - For: Coos Head Timber Co. - Dec. 1959/Feb. 1961 - C.S. File 51/178 & M20-16  
-----  
Find cedar marked for the corner down.  
Set iron pipe post at roots of down cedar for the corner from which:  
16" Fir bears N.42°E., 6.6 ft. orig. BT (scribing visible)  
24" Fir bears S.40°E., 23.2 ft. orig. BT.  
10" Fir bears S.45°W., 22.4 ft. Orig. BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - March 1967 - C.S. File 54/32-47  
-----  
Found - Iron pipe at corner. 1961  
Orig. 16" D.Fir now stump, has been opened, N.42°E., 6.6 ft. "S9T31R9W"  
Orig. 24" D.Fir now stump, S.40°E., 23.2 ft., shows good scar.  
No trace of SW BT.  
Set Brass cap alongside I.P. mkd: COUNTY SURVEYORS T31S R9W  
OFFICE S 8 | S 9  
1967 S17 | S16  
New BTs- 9" W.Fir N.67°E., 55.1 ft. mkd: T31S R9W S9 CS BT.  
9" W.Fir S.2°E., 48.3 ft. mkd: T31S R9W S16 CS BT.