

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8219)

Set a cedar post, 4 ft. long, 4" sq., 24" in the ground, mkd S9 ¼ S on E & S8 ¼ on W faces for the ¼ sec. cor. from which
A fir, 24" dia., bears S.15°E., 34 lks., mkd: S9 ¼ S BT.
A fir, 16" dia., bears S.35°W., 32 lks., mkd: S8 ¼ S BT.

Clifford A. Stephens - For: Coos Head Timber Co. - Jan. 1958
- C.S. File 51/178 & M20-16

Set ½" gal. iron pipe & post, from which:
16" Fir bears S.35°W. (No dist given, rec 32 lks. JC DCSO 9/8/2010)
26" Fir bears S.15°E., 22.4 ft.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & D. West - Feb./March 1967 - C.S. File 54/32-25

Found - Orig. 24" D.Fir now stump, S.15°E., 22.4 ft., found scribe "S 9" shows good scars.
Orig. 16" D.Fir now stump, pushed out of ground, S.35°W., 21.1 ft., opened for scribe "B"
Set - Brass cap at cor. mkd: County Surveyors T31S R9W Office 1967 ¼ S 8|S 9
New BT - 10" Chinq. N.17°W., 35.7 ft. mkd: ¼ S8 CS BT.
No other trees available.
Note - This corner lies about 150.0 ft. north of ridge top.