TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8221)

A fir, 36" dia., mkd. S4 ¼ S on E & S5 ¼ S on W side for the ¼ sec. cor. from which
A fir, 18" dia., bears N.53°E., 15 lks., mkd: S4 ¼ S BT.
A fir, 10" dia., bears S.50°W., 71 lks., mkd: S5 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & D. West - Feb./March 1967 - C.S. File 54/32-24

Found - Orig. 36" corner tree, faces on E & W.
Orig. 18", now 24" D.Fir N.53°E., 9.9 ft. opened for scribe "4"
No trace of SW BT.
Set - Brass cap on E side of corner tree mkd: T31S R9W
COUNTY SURVEYOR OFFICE ¼ S 5|S 4
New BTs- These bear. & dist. are from brass cap which is about 30" East of center of corner tree.

Jerry Estabrook - For: Swanson Group - June 2005 - M148-32

Found - GLO corner tree, vis. scribe E Side
County BCIP bears N.68°16'20"E., 3.18'
24" D.Fir stump bears N.53°E., 9.9' (GLO)
New - 15" D.Fir bears N.30°W., 23.5'
15" D.Fir bears S.39°W., 41.2'
17" D.Fir bears S.3°E., 38.5'