

PRIMARY CORNER DESCRIPTION A P on So. Bdy. Sec. 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records C.S. File 64/76-2)

Set a Chinquapin post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 4, 5, 32 and 33, mkd. T31S R9W S33 on NE.; T32S S4 on SE.; S5 on SW.; and S32 on NW. faces, also 4 notches on E. and 2 notches on W. edges fo same and from which

- A Chinquapin 14" dia., bears N.45°E., 50 lks. dist. mkd. T31S R9W S33 BT.
- A Fir 50" dia., bears S.52°E., 35 lks. dist. mkd. T32S R9W S4 BT.
- A Yew 8" dia., bears S.25°W., 25 lks. dist. mkd. T32S R9W S5 BT.
- A Fir 20" dia., bears N.53°W., 55 lks. dist. mkd. T31S R9W S32 BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12192)

Intersect at the old cor. of secs. 4 and 5, which is a small wooden peg driven in the ground, not marked, witnessed as described by the surveyor general, except that the NW. tree has fallen and no marks were found on the NE. and SE. BTs. I change this cor. to an angle point and perpetuate it as follows: alongside the old cor.

Set an Iron post 3 ft. long, 1" dia., 26" in the ground for angle point, with brass cap mkd: A P

- 1917 from which
- A Chinquapin 18" dia., bears N.45°E., 59 lks. dist. mkd. AP BT (Old BT)
- A Yew 8" dia., bears S.27°W., 29 lks. dist. mkd. AP BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - May 1967 - C.S. File 54/32-86

Found - GLO brass cap, properly mkd. in 1917.
18" Chinquapin, now 18" snag, N.45°E., 38.9 ft., burnt, no scribe visible.
8" Yew now 8", S.27°W., 19.1 ft., faint scribe marks, not legible.
New BTs- 53" D.Fir mkd. "AP CS BT", S.58°E., 23.9 ft.
8" Chinquapin N.83°W., 29.8 ft. mkd. "AP CS BT"
This cor. is 260.7 ft. East of sec. cor. for 4 & 5, T32-9