TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8213)

Set a stone, 24x16x10" 18" in the ground, marked ¼ on N side for the ¼ Sec. cor. from which
A fir, 40" dia., bears N.18°E., 50 lks., mkd: S28 ¼ S BT.
A fir, 6" dia., bears S.75°E., 42 lks., mkd: S33 ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Mike Darby & Wm. Stoffel - May 28, 1963 - C.S. File 53/25-2

Found - Stone at corner, checks for size, marking not found.
Find 40" now 40" fir snag, N.18°E., 33.0 ft., shows good scribing "BT".
SE BT not found.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS ¼ S 28 T31S
OFFICE 1967 S 33 R9W
New BTs- 6" Laurel bears N.65°E., 37.9 ft scribed ¼ S28 CS BT
20" R.Fir bears South 61.0 ft scribed ¼ S33 CS BT.