

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8218)

-----  
A Fir, 4" dia., mkd S9 ¼ S on N, S16 on S for ¼ sec. cor. from which

A fir, 4" dia., bears S.30°E., 25 lks., mkd: S16 ¼ S BT.

A hemlock, 5" dia., bears N.30°W., 19 lks., mkd: S9 ¼ S BT

-----  
Clifford A. Stephens - For: Coos Head Timber Co. - Dec. 1959/Feb. 1961 - C.S. File 51/178 & M20-16

-----  
Post gone - 2 BTs remain & in position as called for in the US Gov't notes.

Set post & ¾" gal. Iron Pipe for the ¼ corner from which:

4" Dead fir stub bears S.30°E., 16.5 ft. (face opened-scribing visible)

8" hemlock bears N.30°W., 12,5 ft. (face not opened)

-----  
Douglas Co. Surveyors Office - John M. Powell - W. Penley - 8/21/1970 - C.S. File 54/32-96

-----  
Found - ¾" Iron pipe, bent over & buried in skid road.

No trace of orig. BTs logged & burnt.

Un-recorded scribed stump S.51½°E., 24.6 ft. scribed "BT ¼"

Set brass cap alongside IP mkd: County Surveyors T31S R9W

Office S 9  
1970 S 16

New BOs- ⅝" I.Rod at base of 22" F. Stump N.25°W., 28.8 ft.

⅝" I.Rod at base of 40" F. Stump S.60°W., 22.0 ft.