

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8201-2)

Marked a Fir, 10" dia., T31S S27 on NE, R9W S34 on SE, S33 on SW and S28 on NW faces, with 1 notch on S and 3 notches on E. edges, for the corner of Secs. 27, 28, 33 and 34, from which
A fir, 24" dia. bears N.15°E. 52 lks. mkd: T31S R9W S27 BT
A fir, 30" dia. bears S.60°E. 12 lks. mkd: T31S R9W S34 BT
A fir, 14" dia. bears S.32°W. 25 lks. mkd: T31S R9W S33 BT
A fir, 12" dia. bears N.58°W. 67 lks. mkd: T31S R9W S28 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - March 1967 - C.S. File 54/32-36

Found - No trace of Corner Tree.
Orig. 24" D.Fir, now stump, N.15°E. 34.3 ft., scribing visible "R9W"
Orig. 30" D.Fir, now stump, S.60°E. 7.9 ft., shows good scar.
Orig. 12" D.Fir, now stump, N.58°W., 44.2 ft., scribe visible but not legible.
Orig. 14" D.Fir, now 18", S.32°W., 16.5 ft., shows good scar.
Set - Brass Cap at Cor. mkd: County Surveyors T31S R9W
Office S 28 | S 27
1967 S 33 | S 34
New BTs- 36" D.Fir S.25°E. 45.0 ft. mkd. T31S R9W S34 CS BT.
No other trees available.
Note - Road bears West 100.0 ft. Yellow Tag on Road.

BLM dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, Group #822, surveyed Aug. 1973 - (DCSO records Vol. 37 Page(s) 15323-4)

The cor., of secs. 27, 28, 33, & 34, perpetuated & recorded by the County Surveyor, in 1967, monumented with an iron post, 1" dia., firmly set, protruding 6" above ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A sawed fir stump, 34" dia., bears N.15°E., 53½ lks., with scribe marks R9W S27 visible on partially healed double blaze. (Record, 52 lks.)
A sawed fir stump, 31" dia., bears S.65°E., 12 lks., with healed double blaze. (Record, S.60°E.)
A fir, 19" dia., bears S.31°W., 25 lks., with healed double blaze. (Record, S.32°W.)

continued next page

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stumpy 17" dia., bears N.57°W., 67 lks. with illegible scribe marks visible on partially healed double blaze. (Record, N.58°W.)
and the remains of a BT mkd, by the County Surveyor
A root hole, bears S.25°E., 68 lks., with a down sawed fir stump alongside. 40" dia. with scribe marks T31S R9W S34 CS BT visible on partially healed blaze.
and new bearing trees
A fir, 4" dia., bears N.52¼°E., 72½ lks., mkd. X BT.
A fir, 6" dia., bears S.27½°E., 99 lks., mkd. X BT.
A fir, 4" dia., bears N.17°W., 42½ lks., mkd. X BT.
The geographic position of the corner of sections 27, 28, 33, and 34, as scaled from the Bone Mountain, Oregon, quadrangle map, published by the USGS in 1954, is as follows:
Latitude 42°50.3'N. Longitude 123°45.6'W.

David Edwards - Crew: Brant Miller & Eric Sprinkle -
2/24/2015 - C.S. file 65/87-4

Found - 1967 D.C.S. brass cap in good condition.
19" dia. Fir w/healed faces bears S.31°W., 16.5 ft.
1973 B.L.M. trees -
15" dia. Fir w/healed face bears S.27½°E., 65.3 ft.
12" dia. Fir stump bears N.17°W., 28.1 ft.
New - A 12" dia. Fir scribed "T31S R9W S27 BT" bears
N.32°E., 6.5 ft.
A six foot steel post is set 2 ft South.
Compass decl. 15°E.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor,
under Group No. 2862; Surveyed Nov./Dec. 2016 - (DCSO records
Vol. 59 Page(s) 23585-6)

The cor. of secs. 27, 28, 33, and 34, perpetuated by Edwards,
in 2015, monumented with an iron post, 1" dia., firmly set,
projecting 5" above the ground, with brass cap (properly) mkd
from which the remains of original bearing trees
A sawed and rotted fir stump, 32" dia., 7 ft. tall, bears
S.65°E., 7.9 ft., with a healed double blaze.
A fir, 27" dia., bears S.27¾°W., 16.5 ft., with a healed
double blaze. (Record, S.31°W.)
and the remains of bearing trees mkd. by Roseberry in 1973
A fir, 20" dia., bears S.27½°E., 65.3 ft., with a healed
blaze.
A sawed fir stump, 17" dia., bears N.17°W., 28.1 ft., with
a healed blaze.
and a bearing tree mkd. by Edwards
continued next page

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 14" dia., bears N.34¾°E., 6.5 ft., with scribe marks T31S R9W S27 BT visible on partially healed blaze.
and a new bearing tree
A fir, 4" dia., bears N.37°W., 7.7 ft., mkd. X at breast height and BT at the base.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
NAD 1983 (2011)
Latitude: 42°50'19.81" N. Longitude: 123°45'40.50" W.