TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8203)

Set a basalt stone 16x8x6", 12" in the ground, mkd. ¼ on W face for ¼ sec. cor., from which
An Alder, 6" dia., bears N.10°E., 36 lks. mkd: S27 ¼ S BT.
An Alder, 10" dia. bears N.13°W., 25 lks. mkd: S28 ¼ S BT.

BLM dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, Group #882, surveyed Aug. 1973 - (DCSO records Vol. 37 Page(s) 15324-5)

Point for the ¼ sec. cor. of secs. 27 & 28, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28", long, 2½" dia., 24" in the ground, with brass cap mkd. T31S R9W

¼
S 28 | S 27
1973

from which
A fir, 55" dia., bears S.72°E., 43 lks., mkd. ¼ S27 BT.
A sawed fir stump, 48" dia., bears N.74°W., 28 lks., mkd: ¼ S28 BT.
No other suitable tree available within limits in Sec. 28.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2862; Surveyed Nov./Dec. 2016 - (DCSO records Vol. 59 Page(s) 23586)

The ¼ sec. cor. of secs. 27 & 28, monumented with an iron post, 2½" dia., firmly set, projecting 2" above the ground, in a collar of stone, with brass cap (properly) mkd.
from which the remains of a BT mkd. by Roseberry in 1973
A fir, 59" dia., bears S.72°E., 28.4 ft., with a healed blaze.
and a new bearing tree
A fir, 9" dia., bears S.38¾°W., 11.2 ft., mkd. ¼ S28 BT.
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.