TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8211)

Set a conglomerate stone, 30x12x8" 20" in the ground, marked ¼ on W face for ¼ Sec. cor. from which
A laurel, 10" dia., bears N.42°W., 58 lks., mkd: ¼ S S4 BT
A fir, 6" dia., bears N.26°E., 25 lks., mkd: S 3 ¼ S BT.

Lorne Swearingen, Robert Dollar Co. - May 1960 - C.S. 51/68

Both orig. BTs were found with scribing visible.
I set 7/8"x30" Hex drill, driven 20" in the ground for corner

Fd. Ok by Jerry Estabrook, 6/2005 - M148-32

Tony Hostetter - For: Plumb Creek - 9/13/2013 - C.S. File 65/80-10

Found - 7/8" drill steel and BT as described by Estabrook in 2005 (M148-32)
New BTs- 11" W.Fir, mkd with "X", BT tag, bears N.48°03'E., 23.5 ft. to 6" spike placed in root collar below tag.
12" Fir mkd with "X", BT tag, bears S.73°57'W., 15.1 ft. to 6" spike placed in root collar below tag.
11" Fir mkd with "X", BT tag, bears N.31°31'W., 31.6 ft. to 6" spike placed in root collar below tag.