

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Secs 27 & 34 (Witness Corner)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8202)

Set a Fir post, 4 ft. long, 4" sq. 24" in ground, mkd. S27 ¼S on N and S34 on S faces, from which
A fir, 8" dia., bears N.40°E., 48 lks., mkd: S27 ¼ S BT.
A hemlock, 16" dia. bears S.50°E., 17 lks. mkd: S34 ¼ S BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Feb/March 1967 - C.S. File 54/32-21

Found - 8" D.Fir now 14" N.40°E., 31.2 ft. opened for scribing "4".
No trace of SE BT.
Set - ¾" I.Rod at ¼ corner as this corner falls in road.
Brass cap for Wit. Cor. mkd:
County Surveyors T31S R9W
Wit. Cor. 20' N ¼ S 27
1967 S 34
New BTs- 15" D.Fir N.30°E., 51.4 ft. mkd: ¼ S27 WC CS BT.
27" D.Fir S.27°W., 14.7 ft. mkd: ¼ S34 WC CS BT.

Douglas Co Surveyors Office - Randall W Smith, Deputy - Stephen J. Flause - John Pike - Oct. 1992 - C.S. 64/32-13

Found - ¾" Iron Rod 18" below road surface. 1967
2½" 1967 DCSO brass cap on a 1½" O.D. I.Pipe, protruding 10" above ground, bears South 20.0 ft. from ¾" I.P. 1967
8" now 14" dia. 3 ft. high D.Fir stump with axe marks, no blazes or scribing visible, bears N.40°E., 31.2 ft. from ¾" IR.
15" now 18" dia. 2 ft. high D.Fir stump, scribe marks "B" found, bears N.30°E., 51.4 ft. from DCSO BC/IP W.C. 1967
27" now 30" dia., down D.Fir root hole bears S.27°W., 14.7 ft. from DCSO BC/IP W.C. BT fell on face. 1967
New BTs- 4" Madrone bark scribed "¼ S27 CS BT" bears N.76½°E. 40.6 ft.
4" D.Fir double blazed & scribed X BT bears S.16½°W., 10.8 ft.
6" D.Fir double blazed and scribed "¼ S27 CS BT" bears N.58½°W., 45.3 ft.