

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8204)

Set Yew post, 4 ft. long, 4" sq., 24" in the ground, marked S22 ¼ S on N & S 27 on S for the ¼ sec. cor. from which
A fir, 8" dia., bears S.15°W., 14 lks., mkd: S27 ¼ S BT.
A W.Fir, 8" dia., bears N.89°W., 17 lks., mkd: S22 ¼ S BT.

Wallace Owen - For: The Robert Dollar Co. - Wit: Robert Harris & Tom Mehl- Sept. 25, 1959 - C.S. File 42/424-2

Found in poor condition. The South BT, 8" Fir bears S.15°W., 14 lks, had fallen over and rotted but scribing was still visible. The point of a Yew Post was found, as described, from the bearing tree. The North Bearing Tree, an 8" W.Fir bears N.89°W. 17 lks. had completely disappeared.
The Corner was marked with 1" Rod driven 18" into the ground.
38" D.Fir N.39½°E., 14 ft. was referenced and scribed ¼ S22 RS 424 BT.
24" D.Fir S.18½°W., 20.9 ft., was referenced & scribed ¼ S27 RS 424 BT.
Bearing trees were referenced with a compass & chain. Magnetic declination used was 19½°E.