TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor.,Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8206)

Marked a fir, 8" dia., S15 ¼S on N & S22 on S for the ¼ sec. cor., from which
A fir, 8" dia., bears N.10°E., 58 lks., mkd: S15 ¼ S BT.
A fir, 8" dia., bears S.25°W., 10 lks., mkd: S22 ¼ S BT.

Reported as not found, DCSO JP 3/1967 C.S. 54/25A

Ron Quimby - Crew: N. Fromdahl & R. Olson - For: Plum Creek Timber Co. - 6/2016 - C.S. File 65/92-11

Corner was established at mid point between fd corners.
Set - 5/8"x30" IR with 2" alum. cap mkd:

¼
S15
S22
2016
RLS 1654

BTs - 8" W.Fir N.59°E., 10.7' scribed "¼ S15 BT"
5" W.Fir S.69°E., 8.9' scribed "¼ S22 BT"
4" W.Fir N.61°W., 10.4' scribed "¼ S15 BT"
15" D.Fir S.71°W., 22.0' scribed