

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 461100

PRIMARY CORNER DESCRIPTION No. 1/4 cor. for Sec. 3 only, T32-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12190)

-----  
Set an Iron post 3 ft. long, 1" dia., 26" in the ground, for ¼ cor. of sec. 3 only, with brass cap mkd.

¼ S 3  
1917

from which

A Fir 7" dia., bears S.87°30'E., 153 lks., mkd. ¼ S3 BT.

A Fir 7" dia., bears S.67°W., 86 lks., mkd. ¼ S3 BT.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2862; Surveyed Nov./Dec. 2016 - (DCSO records Vol. 59 Page(s) 23582)

-----  
The ¼ sec. cor. of sec. 3 only, T. 32 S., R. 9 W., determined at record bearing and distance from a bearing tree mkd. by Mensch and Sorrels in 1917

A fir, 40" dia. bears S.67°W. 56.8 ft. with a healed blaze  
The monument set by Mensch and Sorrels, an iron post, 1" dia., 18" long (Record, 36") with brass cap mkd. ¼ S3 1917, was found lying loose in the root wad of an uprooted tree.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, in a collar of stone, with brass cap mkd.

T31S R9W

¼ S 3

T32S R9W

2016

and a new bearing tree

A fir, 7" dia., bears S.47¼°E., 24.3 ft., mkd. ¼ S3 BT.

Deposit a magnet in a white plastic case at the base and bury the General Land Office iron post horizontally alongside the stainless steel post

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.