

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8193)

Set a Fir post, 4 ft. long, 4" sq., 24" in the ground, marked S26 on E and S27 ¼ S on W faces for ¼ sec. cor. from which
A fir, 10" dia., bears S.85°E., 43 lks., mkd: S26 ¼ S BT.
An Oak, 12" dia., bears S.75°W., 25 lks. mkd: S 27 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones, & J. Brady - March 1967 - C.S. File 54/32-32

Found - 10" D.Fir, now Stump, S.85°E., 28.4 ft., opened for scribe "B".
12" Oak S.75°W. 16.5 ft., this tree down & burnt.
Set - Brass Cap at Cor. Mkd: County Surveyors T31S R9W Office, 1967 ¼ S 27 | S 26
New BTs- 11" D.Fir S.81½°E., 35.3 ft. mkd. ¼ S26 CS BT.
8" D.Fir S.47½°W., 12.2 ft mkd. ¼ S27 CS BT.

Stephan Stys - Crew: Blue James, John rondeau, and Xander Thalheimer - 5/7/2024 filed 5/14/2025 - C.S. File 65/116-2

Found - A 2½" brass cap on a 1" iron pipe (properly mkd) and set per C.S. File 54/32-32.
A 10" rotten fir stump, with no marks bears S.85°E., 28.4' (Per DCSO records Vol. 19 pg 8193).
A 19" Fir stump, stands 5' tall with a healed face and tag bears S.81°30'E. 35.3' (per C.S. 54/32-32)
A 25" Fir, with healed face and tag bears S.47°30'W., 12.2' (per C.S. File 54/32-32)
New - A 22" Fir, faced & scribed "E ¼ S27 BT" with X-chop and tag bears S.3°W., 34.3 to a spike at side center
A 10" Fir, faced & scribed "E ¼ S27 BT" with X-chop and tag bears N.72°W., 16.0 to a spike at side center.
A 14" Fir, faced & scribed "E ¼ S27 BT" with X-chop and tag bears N.51°W., 15.8 to a spike at side center.
Note - LAT. AND LONG. PER GARMIN ETREX HANDHELD GPS
N: 42°50'46.6" W: 123°44'29.2"
GENERAL NOTE:
LAT. AND LONG. ARE FROM A GARMIN ETREX HAND HELD GPS AND DOES NOT PRODUCE SURVEY GRADE COORDINATES.

continued next page

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 2-18-25 - C.S. File 67/60-7

Found - D.C.S.O. 1967 Brass cap projecting 11"
Fir rotted to ground S.85°E. 28.4 ft.
Very rotted 12" oak S.75°W. 16.5 ft.
16"x5 ft sawn D.Fir stump S.81½°E. 35.3 ft fully
healed double blaze. Add 3½" mag nail right side
center.
27" D.Fir S.47¼°W. 11.7 ft (rec 12.2 ft) fully
healed single blaze. Add 3½" mag nail, right side
center.
New - Unrecorded bearing trees scribed by LS86454 12-23
(Stephan Stys) 5/14/2025 See above corner report.
15" D.Fir N.41°W. 15.8 ft scribed E ¼ S 27 BT with
unhealed single blaze.
11"D. Fir N.72°W. 16.0 ft scribed E ¼ S 27 BT with
unhealed single blaze.
23" D.Fir S.3°W. 34.3 ft scribed E ¼ S 27 BT with
unhealed single blaze.
These three trees have 6" spikes left side center,
high bark blaze "X" with blazes painted orange.
Notes - Mon on moderate south slope 70 ft± south of gravel
road. Older clearcut to E., old regrowth to W.

Compass decl. 14½°E.
O CRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N 5028.671 E54634.154