TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8195)

Marked a Chinquapin, 5" dia., S23 on E & S22 ¼ S on W for the sec. cor. from which
A fir, 20" dia., bears S.85°E., 36 lks., mkd: S 23 ¼ S BT.
A chinquapin, 8" dia., bears N.85°W., 36 lks., mkd: S 22 ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones, C. Stone & J. Brady - Feb/March 1967 - C.S. File 54/32-16

Found - 5", now 8" Chinquapin Corner Tree, scar on W. face.
20", now 25" D.Fir S.85°E. 23.8 ft., scribe visible "BT".
8" now 13" Chinq. N.85°W., 23.8 ft. shows good scar.
Set - Brass cap on W side of corner tree mkd: T31S R9W
COUNTY SURVEYORS ¼ S22|S 23
OFFICE 1967
Reblazed & rescribed -
13" chinq. N.85°W., 23.8 ft. mkd: ¼ S22 CS BT.
Note - Orig. notes call for draw at 37.50 ch. I find this to be about 300.0 ft. from draw on small ridge, running SW.

Ron Quimby - Crew: N. Fromdahl & R. Olson - 6/2016 - C.S. File 65/93-14

Found - 1967 DCSO brass cap (properly mkd)
20" chinquapin (corner tree) on east side of brass cap.
22" D.Fir snag S.85°E., 23.8 ft. good scar.
19" chinquapin N.85°W., 23.8 ft. good scar.
New - 8" Fir S.40°W.,18.0 ft. scribed ¼ S22 BT.
Note - Handheld:
Lat. 42°51.655' & Long. 123°44.480'
Compass decl. 15½°E.