

TOWNSHIP 31 RANGE 09 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor SEcs 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars under contract #727, dated December 20, 1900 - (DCSO records Vol. 19 Page(s) 8195)

Set a basalt stone 18x8x6", 12" in the ground for cor. of secs. 14, 15, 22, & 23 mkd 3 notches on the S & 2 notches on the E edges, from which
A fir, 12" dia., bears N.45°E., 128 lks., mkd: T31S R9W S14 BT.
A fir, 8" dia. bears S.8°E., 40 lks., mkd: T31S R9W S23 BT
A fir, 20" dia. bears S.75°W. 60 lks. mkd: T31S R9W S22 BT
A W.Fir, 8" dia., bears N.28°W., 31 lks., mkd: T31S R9W S15 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & E. West - Feb. 1967 - C.S. File 54/32-93

Found - Pieces of Stone at Corner.
Orig. 12", now 29" D.Fir, N.45°E. 84.5 ft., shows good scar.
Orig. 8", now 13 D.Fir, S.8°E., 26.4 ft.
Orig. 20", now 36" D.Fir, S.75°W., 39.6 ft. (slope distance).
Orig. 20", now Dead D.Fir, N.28°W., 20.5 ft., opened for scribing, fd scribe marks but rotten, not legible.
Set - Brass Cap at Cor. Mkd: County Surveyors T31S R9W
Office S 15 | S 14
1967 S 22 | S 23
New BT - 44" D.Fir N.2½°W., 34.7 ft. mkd. T31S R9W S15 CS BT.

Ron Quimby - Crew: N. Fromdahl & R. Olson - For: Plum Creek Timber Co. - 6/2016 - C.S. File 65/92-11

Found - DCS0 Brass cap
28" D.Fir S.8°E., 26.4'. Good scar.
45" D.Fir S.75°W., 39.6' ([slope distance] per DCS0 renewal) good scar.
52" D.Fir N.2°W., 34.7', good scar.
New BT - 10" D.Fir N.37°E., 17.5' scribed "T31S R9W S14 BT".